

Perfect choice for Access Control

Akuvox's A01S access control terminal incorporates door controller and an RFID reader in one standalone device, thus saving your solution costs. Equipped with an RFID reader (125kHz and 13.56MHz) which is capable of handling a majority of cards in wide use currently. A01S is designed to provide you with greater flexibility and security than those traditional access control systems.

***At a Glance***

- Aluminum alloy with toughened glass front;
- Linux operation systems;
- Multi-frequency RFID card reader;
- 20,000 card capacity & 100,000 Event Log;
- Flush-mounted & Wall-mounted;
- IP65 & IK07 for outdoor usage;
- Compatible with Akuvox cloud & ACMS;

Physical & Power

- Front panel: Toughened Glass
- Frame: Aluminum Alloy
- RFID card reader: 13.56MHz & 125kHz
- Relay out: 1
- Inputs: 2
- Wiegand: Support
- Speaker: 1
- Tamper proof alarm: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- 12V DC connector (if not using PoE)
- IP Rating: IP65
- IK Rating: IK07
- Installation: Flush-mounted or Wall-mounted
- Dimension: 86 x 86 x 33 (mm)
- Working Humidity: 10~90%, no condensing
- Working Temperature: -20°C ~ +55°C
- Storage Temperature: -30°C ~ +70°C

• Capacity

- User Capacity: 20,000
- Card Capacity: 20,000
- Event Log: 100,000

• Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Firmware upgrade
- System logs

• Dimension

• Networking

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, TCP, UDP, ICMP, DHCP, ARP

• Door Entry Feature

- Access schedule export/import
- Access level management
- Support switch to reader mode
- Door access logs query and export
- Flexible shift scheduling and attendance management

